

Aten PRO 3000

The network sentinel

PN: PWUP-OL300AP-AZ01B

EAN: 6422956007737

Specifications

Capacity	3000 VA / 2700 W
Type	On line
Input	
Nominal Voltage	230 VAC
Accepted Voltage Range	120-300 VAC (Based on load at 50%) 180-280 VAC (Based on load at 100%)
Frequency Range	40Hz ~ 70 Hz
Power Factor	≥ 0.90 @ nominal voltage (100% load)
Output	
Output Voltage	200/208/220/230/240 VAC*
Voltage Regulation	±1%
Frequency Range (Synchronized Range)	57 ~ 63 Hz
Frequency Range (Battery Mode)	50 Hz or 60Hz ± 0.5 %
Waveform (Batt. Mode)	Pure Sinewave
Harmonic Distortion	≤ 3 % THD (Linear Load) ≤ 6 % THD (Non-linear Load)
Current Crest Ratio	3:1
Transfer Time	
AC Mode to Battery Mode	Zero
Inverter to Bypass	4 ms (Typical)
Efficiency	
To AC Mode	90 % at full charged battery
To Battery Mode	88 % at full charged battery
ECO Mode	95 % at full charged battery
Indicators type	
LCD Display	Load level, Battery level, AC mode, Battery mode, Bypass mode and Fault indicators
Alarm	
Battery Mode	Sounding every 4 seconds

* Derate to 80% of capacity in Frequency converter mode and to 80% when the output voltage is adjusted to 100/200/208VAC



Pure Sine
Wave Output



Zero
Transfer Time



ECO Mode
for energy saving

- True Double Conversion Technology
- Microprocessor control optimizes reliability
- Software Management
- Up to 90% Efficiency Rates
- Converter mode available
- Input power factor correction
- Output Power Factor 0.9
- LCD Display
- USB & RS232 Port Communication
- Smart SNMP card supported
- Tower topology
- Generator compatible

Low Battery	Sounding every second
Overload	Sounding twice every second
Fault	Continuously sounding
Protection	
Outlets type	4 x Schuko Battery Backup & Surge Protection
Full protection	Overload, Discharge & Over-charge protection Input spike protection
Surge rating energy	760 Joules
Environment	
Humidity	20-90 % RH @ 0-40°C (non-condensing)
Noise level	Less than 50dB
Battery	
Battery Type & Number	12V 9Ah x 6
Battery Voltage	12V
Typical Recharge Time	4 hours up to 90% capacity
Charging Voltage	82.1 VDC ± 1%
Charging Current (max.)	1.0 A
Battery Compatibility	PW9123
Running time on battery (minutes)	25% Load - 26 min 50% Load - 10 min 75% Load - 6 min 100% Load - 3 min
Management	
Connection port	RS232 / USB / Intelligent Port



Software capability


Monitor & Control over USB, LAN and Internet (SNMP card optional)

Physical

Product dimensions	421 x 190 x 318 mm
Product weight	27.6 kg
Cable length	1.8 m
Retail pack dimensions	560 x 320 x 460 mm
Retail pack weight	33.1 kg



Running time on battery



Logistics

Carton Box Size (LxWxH)	560 x 320 x 460 mm
Pieces in the Carton Box	1 pcs / ctn
Net & Gross weight / CTN	N.W. / G.W.: 27.6 kg / 33.1 kg



Certificates

